





HS 46		Profilbreite 460 mm		EP 250/2 3+1,5		EP 400/3 3+1,5	
	Gurtbreite	Freie Zone	Abstand	Trommel min.	Kg/m2	Trommel min.	Kg/m2
	500 mm	20 mm	330 mm	Ø315mm	5,8	Ø400mm	6,3
	600 mm	70 mm	330 mm	Ø315mm	6,6	Ø400mm	7,2
	650 mm	95 mm	330 mm	Ø315mm	6,8	Ø400mm	7,5

HS 58		Profilbreite 580 mm		EP 250/2 3+1,5		EP 400/3 3+1,5	
	Gurtbreite	Freie Zone	Abstand	Trommel min.	Kg/m2	Trommel min.	Kg/m2
	600 mm	10 mm	330 mm	Ø315mm	6,9	Ø400mm	7,1
	650 mm	60 mm	330 mm	Ø315mm	7,2	Ø400mm	7,4
	800 mm	110 mm	330 mm	Ø315mm	8,2	Ø400mm	9,0

HS 63		Profilbreite 630 mm		EP 250/2 3+1,5		EP 400/3 3+1,5	
	Gurtbreite	Freie Zone	Abstand	Trommel min.	Kg/m2	Trommel min.	Kg/m2
	650 mm	10 mm	330 mm	Ø315mm	7,2	Ø400mm	7,5
	800 mm	85 mm	330 mm	Ø315mm	8,2	Ø400mm	9,0
	1000 mm	185 mm	330 mm	Ø315mm	10,3	Ø400mm	11,3

HS 75		Profilbreite 750 mm		EP 250/2 3+1,5		EP 400/3 3+1,5	
	Gurtbreite	Freie Zone	Abstand	Trommel min.	Kg/m2	Trommel min.	Kg/m2
	800 mm	25 mm	330 mm	Ø315mm	8,9	Ø400mm	9,7
	1000 mm	125 mm	330 mm	Ø315mm	10,7	Ø400mm	11,3
	1200 mm	225 mm	330 mm	Ø315mm	12,9	Ø400mm	14,1